

KSG SERIES THREE PHASE

G125KT7



PV On-Grid String Inverter



Max. PV Voltage up to 1100V
Type II DC /AC SPD



PLC communication
WiFi / 4G Plug Optional



DC/AC Ratio up to 1.5
IP66 Protection



High Efficiency up to 98.7%
Smaller and Lighter

Model	G125KT7
Input(DC)	
Max.DC Voltage	1100V
Max.Input Current Per MPPT	40A
Max.Short-circuit Current Per MPPT	60A
Start Voltage	350V
MPPT Voltage Range	200-1000V
Nominal Voltage	650V
Number of MPPT	8
Strings Per MPPT	2
Output(AC)	
Nominal AC Output Power	125kW
Max. AC Apparent Power	125kVA
Nominal AC Voltage	230V/400V,3W+PE,3W+N+PE
AC Grid Frequency Range	50/60Hz±5Hz
Max. Output Current	181.2A
Power Factor (cosΦ)	0.8leading-0.8lagging
THDi	< 3% (Nominal Power)
Efficiency	
Max. Efficiency	98.7%
Euro Efficiency	98.5%
Protection Devices	
DC Switch	Yes
Anti-islanding Protection	Yes
Output Over Current Protection	Yes
DC Reverse Polarity Protection	Yes
String Fault Detection	Optional
DC/AC Surge Protection	DC Type II;AC Type II
AC Short Circuit Protection	Yes
AFCI Function	Optional
Night SVG Function	Optional
PID Recovery	Optional
Insulation Detection	Yes
Residual Current Monitoring	Yes
General Specifications	
Dimensions W x H x D	965mm*700mm*355mm
Weight	85kg
Operating Temperature Range	-30~60°C
Cooling Type	Fan Cooling
Max. Operation Altitude	5,000 m (> 4,000 mDerating)
Max. Operating Humidity	0~100%
IP Class	IP66
Noise (dB)	≤75dB
Topology	Transformer less
Communication	RS485/PLC/WIFI/4G
Display	LED , Buletooth+APP

* Kstar is committed to continuous product innovation. Please be aware that parameters are subject to change without prior notice.

**For certificate requirements, please consult Kstar for more information.

KSTAR

Stock code: 002518

AG Holding Building, Airport Road Dubai United Arab Emirates

Phone: +971 4 288 1934 E-mail: info@ian.ae Website: www.ian.ae

